



ZN7-400/1.14

外形及安装尺寸图

ZN7-400/1.14		
额定工作电流 (A)	Rated Working Current (A)	400
额定工作电压 (V)	Rated Working Voltage (V)	1140/660
极限通断能力 (KA)	Limited Making Capacity (KA)	7.5/9
固有分闸时间 (ms)	Inherent Opening Time (ms)	≤ 30
合闸时间 (ms)	Closing Time (ms)	≤ 100
合闸弹跳时间 (ms)	Closing Bounce Time (ms)	≤ 2
机械寿命 (次)	Mechanical Life (times)	2 × 10 ⁴
电寿命 (次)	Electrical Life (times)	3 × 10 ³
参考重量 (kg)	Weight (kg)	18
合闸电源电压 (V)	Closing Power Supply Voltage (V)	127
欠压、分励直流电源 (V)	Under Voltage、Shunt Release DC Supply (V)	48
合闸功率 (W) (瞬态)	Closing power (W transient)	1152
分闸功率 (W)	Opening power (W)	31
欠压功率 (W)	Under-voltage power (W)	5
辅助触点: 四对常开, 四对常闭	Auxiliary contact: Four NO, Four NC	
辅助触点容量	Auxiliary contact capacitance	AC-15: Ue: AC380V Ie: 1A DC-13: Ue: DC250V Ie: 0.8A